

When the 'ConectionSetWeight' cell has no data in 'PSD for Config', currently you put 0.0 kg in the Datasheet, but we want to delete this column including its title "Connection Set Weight".

【Example】

When we select size name 'CN40T-F40 0.25kW 2P-220VT60Hz-2', currently our customized datasheet indicate Connection Set Weight 0.0 kg

ShinMaywa
Brighten Your Future

Technical Specifications of SUBMERSIBLE PUMP

Model: **CN40T-F40 0.25kW 2P-220VT60Hz-2**

Pump			
Discharge Size	40.00 mm	Weight	15.5 kg (excluding cable)
Impeller type	Channel type, Semi-Open	Impeller Number	2
Max. Solid Passage Dia.	20.00 mm (Soft Solid)	Handling Liquid Temp.	0.0 °C to 32 °C
		Connection Set Weight	0.0 kg
Motor			
Type	Air-filled Submersible Motor	Output	0.25 kW
Number of Poles	2	Insulation Class	E
Rated Voltage	220 V, 3 phase	Starting Method	Direct
Rated Current	1.5 A	Starting Current	7.7 A
Power Cable	VCT 1.25 mm ² x 4 Cores x O.D. 11.5 mm x Standard Length 6 m		
Thermal Protector	Auto-Reset		
Leakage Detector	None		

Please change to delete this column as follows.

ShinMaywa
Brighten Your Future

Technical Specifications of SUBMERSIBLE PUMP

Model: **CN40T-F40 0.25kW 2P-220VT60Hz-2**

Pump			
Discharge Size	40.00 mm	Weight	15.5 kg (excluding cable)
Impeller type	Channel type, Semi-Open	Impeller Number	2
Max. Solid Passage Dia.	20.00 mm (Soft Solid)	Handling Liquid Temp.	0.0 °C to 32 °C
Motor			
Type	Air-filled Submersible Motor	Output	0.25 kW
Number of Poles	2	Insulation Class	E
Rated Voltage	220 V, 3 phase	Starting Method	Direct
Rated Current	1.5 A	Starting Current	7.7 A
Power Cable	VCT 1.25 mm ² x 4 Cores x O.D. 11.5 mm x Standard Length 6 m		
Thermal Protector	Auto-Reset		
Leakage Detector	None		