

SPECIFICATIONS ShinMaywa SUBMERSIBLE PUMP		Model CNMJ80-P80B	Q'ty																								
		Equipment Name	set(s)																								
1. PUMP <table style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 40%;">Pump model</td><td style="width: 60%;">CNMJ80</td></tr> <tr><td>Discharge bore</td><td>80 mm</td></tr> <tr><td>Capacity</td><td>m³/min</td></tr> <tr><td>Total head</td><td>m</td></tr> <tr><td>Weight (excluding cable)</td><td>69 kg</td></tr> <tr><td>Impeller type</td><td>Channel type, Semi-Open</td></tr> <tr><td>Impeller No. (Solid passage dia.)</td><td></td></tr> <tr><td colspan="2" style="text-align: center;"> ☐ 50Hz #1 (80 mm) ☐ 60Hz #2 (80 mm) </td></tr> </table>				Pump model	CNMJ80	Discharge bore	80 mm	Capacity	m ³ /min	Total head	m	Weight (excluding cable)	69 kg	Impeller type	Channel type, Semi-Open	Impeller No. (Solid passage dia.)		☐ 50Hz #1 (80 mm) ☐ 60Hz #2 (80 mm)									
Pump model	CNMJ80																										
Discharge bore	80 mm																										
Capacity	m ³ /min																										
Total head	m																										
Weight (excluding cable)	69 kg																										
Impeller type	Channel type, Semi-Open																										
Impeller No. (Solid passage dia.)																											
☐ 50Hz #1 (80 mm) ☐ 60Hz #2 (80 mm)																											
2. GUIDE RAIL INSTALLATION <table style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 40%;">Guide rail installation code No.</td><td style="width: 60%;">P80B</td></tr> <tr><td>Guide rail installation set weight</td><td>31.5 kg</td></tr> <tr><td>Automatic connection weight</td><td>18 kg</td></tr> </table>				Guide rail installation code No.	P80B	Guide rail installation set weight	31.5 kg	Automatic connection weight	18 kg																		
Guide rail installation code No.	P80B																										
Guide rail installation set weight	31.5 kg																										
Automatic connection weight	18 kg																										
3. MOTOR <table style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 40%;">Type</td><td style="width: 60%;">Air-filled Submersible Motor</td></tr> <tr><td>Output</td><td>2.2 kW</td></tr> <tr><td>Poles</td><td>4 P</td></tr> <tr><td>Insulation class</td><td>F</td></tr> <tr><td>Power supply</td><td>Three phase</td></tr> <tr><td>Starting method</td><td>Direct</td></tr> <tr><td>Protector</td><td>Thermal Protector (Auto-reset type / Standard)</td></tr> <tr><td>Voltage & Current</td><td></td></tr> <tr> <td> ☐ 50Hz ☐ 380 5.4 27.9 ☐ 400 5.2 26.5 ☐ 415 5.0 25.6 ☐ 440 4.7 24.1 ☐ ☐ </td><td> ☐ 60Hz ☐ 380 5.2 23.5 ☐ 400 4.9 24.7 ☐ 440 4.5 27.1 ☐ 460 4.3 28.4 ☐ ☐ </td></tr> <tr> <td style="width: 40%;">Voltage(V)</td><td style="width: 60%;">380 400 440 460</td></tr> <tr> <td>Rated (A)</td><td>5.2 4.9 4.5 4.3</td></tr> <tr> <td>Starting (A)</td><td>23.5 24.7 27.1 28.4</td></tr> </table>				Type	Air-filled Submersible Motor	Output	2.2 kW	Poles	4 P	Insulation class	F	Power supply	Three phase	Starting method	Direct	Protector	Thermal Protector (Auto-reset type / Standard)	Voltage & Current		☐ 50Hz ☐ 380 5.4 27.9 ☐ 400 5.2 26.5 ☐ 415 5.0 25.6 ☐ 440 4.7 24.1 ☐ ☐ 	☐ 60Hz ☐ 380 5.2 23.5 ☐ 400 4.9 24.7 ☐ 440 4.5 27.1 ☐ 460 4.3 28.4 ☐ ☐ 	Voltage(V)	380 400 440 460	Rated (A)	5.2 4.9 4.5 4.3	Starting (A)	23.5 24.7 27.1 28.4
Type	Air-filled Submersible Motor																										
Output	2.2 kW																										
Poles	4 P																										
Insulation class	F																										
Power supply	Three phase																										
Starting method	Direct																										
Protector	Thermal Protector (Auto-reset type / Standard)																										
Voltage & Current																											
☐ 50Hz ☐ 380 5.4 27.9 ☐ 400 5.2 26.5 ☐ 415 5.0 25.6 ☐ 440 4.7 24.1 ☐ ☐ 	☐ 60Hz ☐ 380 5.2 23.5 ☐ 400 4.9 24.7 ☐ 440 4.5 27.1 ☐ 460 4.3 28.4 ☐ ☐ 																										
Voltage(V)	380 400 440 460																										
Rated (A)	5.2 4.9 4.5 4.3																										
Starting (A)	23.5 24.7 27.1 28.4																										
4. ACCESSORIES (1) Cable : VCT 1.25 mm² x 4 cores x φ11.5 mm x Length: 8 m 1 pc. ☐ Leakage detector (Cable: 2PNCT 2.0 mm² x 1 core x φ6.5 mm ... 1 pc.) (Option) ☐ Thermal switch (Cable: 2PNCT 1.25 mm² x 2 cores x φ9.8 mm ... 1 pc.) (Option) (2) Air vent valve 1 pc. (3) Guide Rail Installation Set <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Automatic connection ... 1 pc.</td> <td style="width: 50%;">Sliding bracket 1 pc.</td> </tr> <tr> <td>Guide holder 1 pc.</td> <td>Lifting chain (6 m, with shackle) 1 pc.</td> </tr> </table> ☐ Others _____ ☐ Others _____				Automatic connection ... 1 pc.	Sliding bracket 1 pc.	Guide holder 1 pc.	Lifting chain (6 m, with shackle) 1 pc.																				
Automatic connection ... 1 pc.	Sliding bracket 1 pc.																										
Guide holder 1 pc.	Lifting chain (6 m, with shackle) 1 pc.																										



DWG.	T.Tachibanaki	02/06/'16
JUDG.	M.Hashimoto	02/06/'16
APPD.	M.Tarui	02/06/'16

ShinMaywa Industries, Ltd. Japan
Fluid Division, Ono-Plant

DWG No.
S407069