

SPECIFICATIONS ShinMaywa SUBMERSIBLE PUMP	Model	CNMJ80-F80	Q'ty
	Equipment Name		set(s)

1. PUMP

Pump model	CNMJ80	
Discharge bore	80	mm
Capacity		m ³ /min
Total head		m
Weight (excluding cable)	63	kg
Impeller type	Channel type, Semi-Open	
Impeller No. (Solid passage dia.)	50Hz #1 (80 mm)	

2. DISCHARGE FLANGE

Discharge flange code No.	F80	
Discharge flange set weight	9.5	kg

3. MOTOR

Type	Air-filled Submersible Motor	
Output	1.5	kW
Poles	4	P
Insulation class	F	
Power supply	Three phase	
Starting method	Direct	
Protector	Thermal Protector (Auto-reset type / Standard)	

Voltage & Current

50Hz

☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
380	400	415	440			Voltage(V)							
3.7	3.5	3.4	3.2			Rated (A)							
17.9	17.0	16.4	15.5			Starting (A)							

4. ACCESSORIES

(1) Cable : VCT 1.25 mm² x 4 cores x φ11.5 mm x Length: 8 m 1 pc.

☐ Leakage detector (Cable: 2PNCT 2.0 mm² x 1 core x φ6.5 mm ... 1 pc.) (Option)

☐ Thermal switch (Cable: 2PNCT 1.25 mm² x 2 cores x φ9.8 mm ... 1 pc.) (Option)

(2) Air vent valve 1 pc.

(3) Discharge flange

☐ Others _____

☐ Others _____

