

SPECIFICATIONS			Model CNMJ100-F80		Q'ty																															
ShinMaywa SUBMERSIBLE PUMP			Equipment Name		set(s)																															
1. PUMP <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40%;">Pump model</td> <td style="width: 60%;">CNMJ100</td> </tr> <tr> <td>Discharge bore</td> <td>80 mm</td> </tr> <tr> <td>Capacity</td> <td>m³/min</td> </tr> <tr> <td>Total head</td> <td>m</td> </tr> <tr> <td>Weight (excluding cable)</td> <td>105 kg</td> </tr> <tr> <td>Impeller type</td> <td>Channel type, Semi-Open</td> </tr> <tr> <td>Impeller No. (Solid passage dia.)</td> <td> ☐ 50Hz #1 (80 mm) ☐ 60Hz #2 (80 mm) </td> </tr> </table>							Pump model	CNMJ100	Discharge bore	80 mm	Capacity	m ³ /min	Total head	m	Weight (excluding cable)	105 kg	Impeller type	Channel type, Semi-Open	Impeller No. (Solid passage dia.)	☐ 50Hz #1 (80 mm) ☐ 60Hz #2 (80 mm)																
Pump model	CNMJ100																																			
Discharge bore	80 mm																																			
Capacity	m ³ /min																																			
Total head	m																																			
Weight (excluding cable)	105 kg																																			
Impeller type	Channel type, Semi-Open																																			
Impeller No. (Solid passage dia.)	☐ 50Hz #1 (80 mm) ☐ 60Hz #2 (80 mm)																																			
2. DISCHARGE FLANGE <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40%;">Discharge flange code No.</td> <td style="width: 60%;">F80</td> </tr> <tr> <td>Discharge flange set weight</td> <td>9.5 kg</td> </tr> </table>							Discharge flange code No.	F80	Discharge flange set weight	9.5 kg																										
Discharge flange code No.	F80																																			
Discharge flange set weight	9.5 kg																																			
3. MOTOR <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40%;">Type</td> <td style="width: 60%;">Air-filled Submersible Motor</td> </tr> <tr> <td>Output</td> <td>5.5 kW</td> </tr> <tr> <td>Poles</td> <td>4 P</td> </tr> <tr> <td>Insulation class</td> <td>F</td> </tr> <tr> <td>Power supply</td> <td>Three phase</td> </tr> <tr> <td>Starting method</td> <td>Direct</td> </tr> <tr> <td>Protector</td> <td>Thermal Protector (Auto-reset type / Standard)</td> </tr> <tr> <td colspan="2">Voltage & Current</td> </tr> <tr> <td style="text-align: center;">☒ 50Hz</td> <td style="text-align: center;">☒ 60Hz</td> </tr> <tr> <td style="text-align: center;">☐ ☐ ☐ ☐ ☐ ☐</td> <td style="text-align: center;">☐ ☐ ☐ ☐ ☐ ☐</td> </tr> <tr> <td style="text-align: center;">380 400 415 440 </td> <td style="text-align: center;">380 400 440 460 </td> </tr> <tr> <td style="text-align: center;">13.2 12.6 12.1 11.4 </td> <td style="text-align: center;">12.9 12.3 11.2 10.7 </td> </tr> <tr> <td style="text-align: center;">71.8 68.3 65.8 62 </td> <td style="text-align: center;">59.7 56.7 62.4 65.2 </td> </tr> <tr> <td style="text-align: center;">Voltage(V)</td> <td style="text-align: center;">Rated (A)</td> </tr> <tr> <td style="text-align: center;">Starting (A)</td> <td style="text-align: center;">Starting (A)</td> </tr> </table>							Type	Air-filled Submersible Motor	Output	5.5 kW	Poles	4 P	Insulation class	F	Power supply	Three phase	Starting method	Direct	Protector	Thermal Protector (Auto-reset type / Standard)	Voltage & Current		☒ 50Hz	☒ 60Hz	☐ ☐ ☐ ☐ ☐ ☐	☐ ☐ ☐ ☐ ☐ ☐	380 400 415 440	380 400 440 460	13.2 12.6 12.1 11.4	12.9 12.3 11.2 10.7	71.8 68.3 65.8 62	59.7 56.7 62.4 65.2	Voltage(V)	Rated (A)	Starting (A)	Starting (A)
Type	Air-filled Submersible Motor																																			
Output	5.5 kW																																			
Poles	4 P																																			
Insulation class	F																																			
Power supply	Three phase																																			
Starting method	Direct																																			
Protector	Thermal Protector (Auto-reset type / Standard)																																			
Voltage & Current																																				
☒ 50Hz	☒ 60Hz																																			
☐ ☐ ☐ ☐ ☐ ☐	☐ ☐ ☐ ☐ ☐ ☐																																			
380 400 415 440	380 400 440 460																																			
13.2 12.6 12.1 11.4	12.9 12.3 11.2 10.7																																			
71.8 68.3 65.8 62	59.7 56.7 62.4 65.2																																			
Voltage(V)	Rated (A)																																			
Starting (A)	Starting (A)																																			
4. ACCESSORIES (1) Cable : VCT 2.0 mm² x 4 cores x φ12.0 mm x Length: 8 m 1 pc. ☐ Leakage detector (Cable: 2PNCT 2.0 mm² x 1 core x φ6.5 mm ... 1 pc.) (Option) ☐ Thermal switch (Cable: 2PNCT 1.25 mm² x 2 cores x φ9.8 mm ... 1 pc.) (Option) (2) Air vent valve 1 pc. (3) Discharge flange ☐ Others _____ ☐ Others _____																																				



DWG.	T.Tachibanaki	02/06/'16
JUDG.	M.Hashimoto	02/06/'16
APPD.	M.Tarui	02/06/'16

ShinMaywa Industries, Ltd. Japan
Fluid Division, Ono-Plant

DWG No.
S407076