

SPECIFICATIONS			Model CNMJ100-F80		Q'ty																																																																																	
ShinMaywa SUBMERSIBLE PUMP			Equipment Name		set(s)																																																																																	
1. PUMP <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Pump model</td> <td style="width: 50%;">CNMJ100</td> </tr> <tr> <td>Discharge bore</td> <td>80 mm</td> </tr> <tr> <td>Capacity</td> <td>m³/min</td> </tr> <tr> <td>Total head</td> <td>m</td> </tr> <tr> <td>Weight (excluding cable)</td> <td>116 kg</td> </tr> <tr> <td>Impeller type</td> <td>Channel type, Semi-Open</td> </tr> <tr> <td colspan="2">Impeller No. (Solid passage dia.)</td> </tr> <tr> <td colspan="2" style="text-align: center;"> ☐ 50Hz #1 (80 mm) ☐ 60Hz #2 (80 mm) </td> </tr> </table>							Pump model	CNMJ100	Discharge bore	80 mm	Capacity	m ³ /min	Total head	m	Weight (excluding cable)	116 kg	Impeller type	Channel type, Semi-Open	Impeller No. (Solid passage dia.)		☐ 50Hz #1 (80 mm) ☐ 60Hz #2 (80 mm)																																																																	
Pump model	CNMJ100																																																																																					
Discharge bore	80 mm																																																																																					
Capacity	m ³ /min																																																																																					
Total head	m																																																																																					
Weight (excluding cable)	116 kg																																																																																					
Impeller type	Channel type, Semi-Open																																																																																					
Impeller No. (Solid passage dia.)																																																																																						
☐ 50Hz #1 (80 mm) ☐ 60Hz #2 (80 mm)																																																																																						
2. DISCHARGE FLANGE <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Discharge flange code No.</td> <td style="width: 50%;">F80</td> </tr> <tr> <td>Discharge flange set weight</td> <td>9.5 kg</td> </tr> </table>							Discharge flange code No.	F80	Discharge flange set weight	9.5 kg																																																																												
Discharge flange code No.	F80																																																																																					
Discharge flange set weight	9.5 kg																																																																																					
3. MOTOR <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Type</td> <td style="width: 50%;">Air-filled Submersible Motor</td> </tr> <tr> <td>Output</td> <td>7.5 kW</td> </tr> <tr> <td>Poles</td> <td>4 P</td> </tr> <tr> <td>Insulation class</td> <td>F</td> </tr> <tr> <td>Power supply</td> <td>Three phase</td> </tr> <tr> <td>Starting method</td> <td>Direct</td> </tr> <tr> <td colspan="2">Protector Thermal Protector (Auto-reset type / Standard)</td> </tr> <tr> <td colspan="2">Voltage & Current</td> </tr> <tr> <td colspan="2"> ☐ 50Hz ☐ 60Hz </td> </tr> <tr> <td colspan="2"> <table style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td></td><td></td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td> </tr> <tr> <td>380</td><td>400</td><td>415</td><td>440</td><td></td><td></td><td>Voltage(V)</td><td>380</td><td>400</td><td>440</td><td>460</td><td></td><td></td><td></td><td></td> </tr> <tr> <td>17.8</td><td>16.9</td><td>16.3</td><td>15.4</td><td></td><td></td><td>Rated (A)</td><td>17.5</td><td>16.7</td><td>15.1</td><td>14.5</td><td></td><td></td><td></td><td></td> </tr> <tr> <td>107</td><td>101</td><td>97.7</td><td>92.1</td><td></td><td></td><td>Starting (A)</td><td>94.5</td><td>89.8</td><td>98.8</td><td>103</td><td></td><td></td><td></td><td></td> </tr> </table> </td> </tr> </table>							Type	Air-filled Submersible Motor	Output	7.5 kW	Poles	4 P	Insulation class	F	Power supply	Three phase	Starting method	Direct	Protector Thermal Protector (Auto-reset type / Standard)		Voltage & Current		☐ 50Hz ☐ 60Hz		<table style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td></td><td></td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td> </tr> <tr> <td>380</td><td>400</td><td>415</td><td>440</td><td></td><td></td><td>Voltage(V)</td><td>380</td><td>400</td><td>440</td><td>460</td><td></td><td></td><td></td><td></td> </tr> <tr> <td>17.8</td><td>16.9</td><td>16.3</td><td>15.4</td><td></td><td></td><td>Rated (A)</td><td>17.5</td><td>16.7</td><td>15.1</td><td>14.5</td><td></td><td></td><td></td><td></td> </tr> <tr> <td>107</td><td>101</td><td>97.7</td><td>92.1</td><td></td><td></td><td>Starting (A)</td><td>94.5</td><td>89.8</td><td>98.8</td><td>103</td><td></td><td></td><td></td><td></td> </tr> </table>		☐	☐	☐	☐	☐	☐			☐	☐	☐	☐	☐	☐	☐	380	400	415	440			Voltage(V)	380	400	440	460					17.8	16.9	16.3	15.4			Rated (A)	17.5	16.7	15.1	14.5					107	101	97.7	92.1			Starting (A)	94.5	89.8	98.8	103				
Type	Air-filled Submersible Motor																																																																																					
Output	7.5 kW																																																																																					
Poles	4 P																																																																																					
Insulation class	F																																																																																					
Power supply	Three phase																																																																																					
Starting method	Direct																																																																																					
Protector Thermal Protector (Auto-reset type / Standard)																																																																																						
Voltage & Current																																																																																						
☐ 50Hz ☐ 60Hz																																																																																						
<table style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td></td><td></td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td> </tr> <tr> <td>380</td><td>400</td><td>415</td><td>440</td><td></td><td></td><td>Voltage(V)</td><td>380</td><td>400</td><td>440</td><td>460</td><td></td><td></td><td></td><td></td> </tr> <tr> <td>17.8</td><td>16.9</td><td>16.3</td><td>15.4</td><td></td><td></td><td>Rated (A)</td><td>17.5</td><td>16.7</td><td>15.1</td><td>14.5</td><td></td><td></td><td></td><td></td> </tr> <tr> <td>107</td><td>101</td><td>97.7</td><td>92.1</td><td></td><td></td><td>Starting (A)</td><td>94.5</td><td>89.8</td><td>98.8</td><td>103</td><td></td><td></td><td></td><td></td> </tr> </table>		☐	☐	☐	☐	☐	☐			☐	☐	☐	☐	☐	☐	☐	380	400	415	440			Voltage(V)	380	400	440	460					17.8	16.9	16.3	15.4			Rated (A)	17.5	16.7	15.1	14.5					107	101	97.7	92.1			Starting (A)	94.5	89.8	98.8	103																													
☐	☐	☐	☐	☐	☐			☐	☐	☐	☐	☐	☐	☐																																																																								
380	400	415	440			Voltage(V)	380	400	440	460																																																																												
17.8	16.9	16.3	15.4			Rated (A)	17.5	16.7	15.1	14.5																																																																												
107	101	97.7	92.1			Starting (A)	94.5	89.8	98.8	103																																																																												
4. ACCESSORIES (1) Cable : VCT 3.5 mm² x 4 cores x φ14.0 mm x Length: 8 m 1 pc. ☐ Leakage detector (Cable: 2PNCT 2.0 mm² x 1 core x φ6.5 mm ... 1 pc.) (Option) ☐ Thermal switch (Cable: 2PNCT 1.25 mm² x 2 cores x φ9.8 mm ... 1 pc.) (Option) (2) Air vent valve 1 pc. (3) Discharge flange ☐ Others _____ ☐ Others _____																																																																																						



DWG.	T.Tachibanaki	02/06/'16
JUDG.	M.Hashimoto	02/06/'16
APPD.	M.Tarui	02/06/'16

ShinMaywa Industries, Ltd. Japan
Fluid Division, Ono-Plant

DWG No.
S407077