

SPECIFICATIONS ShinMaywa SUBMERSIBLE PUMP	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Model</td> <td style="width: 70%;">CNMJ80-P100B</td> </tr> <tr> <td>Equipment Name</td> <td></td> </tr> </table>	Model	CNMJ80-P100B	Equipment Name		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Q'ty</td> </tr> <tr> <td>set(s)</td> </tr> </table>	Q'ty	set(s)
Model	CNMJ80-P100B							
Equipment Name								
Q'ty								
set(s)								

1. PUMP

Pump model	CNMJ80
Discharge bore	100 mm
Capacity	m ³ /min
Total head	m
Weight (excluding cable)	69 kg
Impeller type	Channel type, Semi-Open
Impeller No. (Solid passage dia.)	
	☐ 50Hz #1 (80 mm) ☐ 60Hz #2 (80 mm)

2. GUIDE RAIL INSTALLATION

Guide rail installation code No.	P100B
Guide rail installation set weight	40.5 kg
Automatic connection weight	27 kg

3. MOTOR

Type	Air-filled Submersible Motor
Output	2.2 kW
Poles	4 P
Insulation class	F
Power supply	Three phase
Starting method	Direct
Protector	Thermal Protector (Auto-reset type / Standard)
Voltage & Current	
☐ 50Hz	☐ 60Hz
☐ ☐ ☐ ☐ ☐ ☐	☐ ☐ ☐ ☐ ☐ ☐
380 400 415 440 Voltage(V)	380 400 440 460
5.4 5.2 5.0 4.7 Rated (A)	5.2 4.9 4.5 4.3
27.9 26.5 25.6 24.1 Starting (A)	23.5 24.7 27.1 28.4

4. ACCESSORIES

(1) Cable : VCT 1.25 mm² x 4 cores x φ11.5 mm x Length: 8 m 1 pc.

☐ Leakage detector (Cable: 2PNCT 2.0 mm² x 1 core x φ6.5 mm ... 1 pc.) (Option)

☐ Thermal switch (Cable: 2PNCT 1.25 mm² x 2 cores x φ9.8 mm ... 1 pc.) (Option)

(2) Air vent valve 1 pc.

(3) Guide Rail Installation Set

Automatic connection ... 1 pc.	Sliding bracket 1 pc.
Guide holder 1 pc.	Lifting chain (6 m, with shackle) 1 pc.

☐ Others _____

☐ Others _____



DWG.	T.Tachibanaki	02/06/'16
JUDG.	M.Hashimoto	02/06/'16
APPD.	M.Tarui	02/06/'16

ShinMaywa Industries, Ltd. Japan
Fluid Division, Ono-Plant

DWG No.
S407079